



**ULTRASUPER**  
Construction Chemical



### Registered Office

Plot No. 16, Bharatpur Road Mathura  
Mathura (Uttar Pradesh)-281001  
INDIA

### Sole Distributor For Nepal

Elite Traders Pvt. Ltd.

📍 Sokedhara-4, Kathmandu, Nepal

✉ sales.etpln@gmail.com, Website: www.etpln.com

☎ 01-4650186, +977-9849904677



## Table of Contents

01

About us

02

Admixture

03

Grouts and  
Waterproofing  
& Bonding  
Agent

04

OTHER  
CONCRETE  
SOLUTIONS

05

Protecting  
Coating

06

Surface  
Treatment

07

Sealants

08

Certificates



## ABOUT US

UltraSuper Chemicals Company is a company with innovative technology and advanced construction chemical and allied products offering leading edge to the construction industry. Our aim is to contribute actively in improving productivity, continuous innovation, R & D and solution centric customer satisfaction. The products we offer provide the customer with maximum value in performance, quality, comfort, safety, flexibility and overall economy. Our operation focuses on products and solutions with high technology content that offer customer a distinct added value. Packing innovation - using re-cyclable material and alternative products is on priority. High performance innovative solution - UltraSuper will continuously interact with customers in order to deliver high performance products and service to ensure that customer and business associates feel the satisfaction with our association.



Product Name	Product Description	Usage of Product	Dosages/ Coverage/Yield	Pack Size
Ultrasuper 58001	High performance PCE based admixture for the wide range of concrete grades	Ultrasuper 58001 is a water reducing admixture conform to IS:9103-1999, its also conforms to ASTM C-494 type F and G	0.5 to 1.2 liter per 100 kg of total cementitious material	230 kg, 225 kg in Drum or Bulk tanker
Ultrasuper 58002	High Range water reducing and long term dispersibility & retention based on modified Polycarboxylic either Superplasticiser conforms to IS 9103:1999 ASTM C 494 Type G	Speeds of construction, increases work ability and cohesion aids pumping by reducing line friction dry packing. Low porosity improved water penetration resistance.	0.4 to 1.2% by weight of total cementitious material	230 kg, 225 kg in Drum or Bulk tanker
Ultrasuper 58003	Advanced low viscosity high performance superplasticiser, based on polycarboxylic technology complies with IS 9103:1999 (2007) also complies with ASTM C 494 Type G.	Ultrasuper 58003 is high performance superplasticiser intended for application where high water reduction and long work ability retention are required and it has been developed for used in self compacting concrete.	0.4 to 1.1% by weight of total cementitious material	230 kg, 225 kg in Drum or Bulk tanker
Ultra super R2605	Water Reducing retarding Admixture	Complies with BS 5075 part-1 and with ASTM C494 as type B & Type-D Control of stiffening improves slip forming and assists in preventing the formation of cold joints in large pours.	0.3 to 0.60 liter per 100 kg of total cementitious material	230 kg, 225 kg in Drum or Bulk tanker
ULTRASUPER AWR	ULTRASUPER AWR is an Air Entraining And Water Reducing Admixture	Increase Placebility gives stable Air voids system compacted durable concrete resistant to extreme thermal variation and frost action	100 50 250ml per 50 kgs of cementitious material	230 kg, 225 kg in Drum or Bulk tanker
ULTRASUPER ACF	Chloride free Accelerating Admixture	To Accelerate the setting & hardening of Concrete. Usefull in cold weather concreting and for short create Concrete	02 to 04 % of total Cementitious Material	230 kg, 225 kg in Drum or Bulk tanker





Admixture

Product Name	Product Description	Usage of Product	Dosages/ Coverage/Yield	Pack Size
Ultra super-FA	High range water reducing admixture based on a blend of sulphonate naphthalene formaldehyde and other polymers to be used as a superplasticizer, Conforms to IS: 9103-1999,(reaffirmed 2004), Edition 2.2 (2007- 2008), ASTM C494/C494 M-08a, Type F & A, & BS EN 934.	Produces low to medium grade pumpable concrete with moderate dosage; Used with higher dosage for High grade of concrete where early and later strength gain is required.	0.8% to 1.5% By weight of cement depending upon water reduction slump retention and strength.	1, 5, 20 & 250 kg
Ultra Super GFM	High range water reducer super plasticizer giving large water reduction at a given workability, Conforms to IS: 9103-1999 (reaffirmed 2004), Edition 2.2 (2007- 2008), ASTM C494/C494 M-08a, Type F&G, & BS EN 934.	For higher grade pumpable concrete with minimum 2 hrs. slump retention (Especially for RMC), For mass concrete where excessive retardation and low heat of hydration is desirable.	0.8% to 1.5% by wt. of cement depending upon the requirement of water reduction, slump retention & set retardation.	20, 50 & 250 kg
Ultra Super GFH	High range water reducer superplasticizer based on a blend of sulphonated naphthalene formaldehyde giving large water reduction at a given workability, Conforms to IS: 9103-1999,(reaffirmed 2004), Edition 2.2 (2007- 2008), ASTM C494/C494M-08a, Type F & G, & BS EN 934.	For medium grade pumpable concrete with minimum 2 hrs. slump retention (Especially for RMC), For mass concrete where excessive retardation and low heat of hydration is desirable.	0.8% to 1.5% by wt. of cement depending upon the requirement of water reduction, slump retention & set retardation.	20, 50 & 250 kg
Ultra Super-P	Finely modified accelerating and waterproofing shotcrete admixtures in powder form.	For sprayed concrete and mortar in galleries, tunnels, retaining walls, embankments, tank lining etc. Apocrete Shot P sets rapidly hence gives good water tightness in the sprayed concrete.	1 to 4 kg of Ultra Super-P powder is used per 50kg bag of cement.	25 Kg HDPEBags
ULTRASUPER LAF	Completely alkali free accelerator available in liquid form for use with sprayed concrete for guniting, shotcreting etc, Conforms to IS 9103-1999 (reaffirmed 2004) Edition 2.2 (2007- 2008), ASTM C494/C494- 08a, Type C, BS EN 934 and Enfacr Specification of sprayed concrete.	For sprayed concrete and mortar in galleries,tunnels, retaining walls, embankments, tank lining etc. Cement mortar admixed with ULTRASUPER LAF - LAF sets rapidly; hence faster placing of higher thickness in one application is possible.	4%to 10% by wt.of cement depending upon the site requirement and ambient temperature.	250 kg drums



Grouts and Waterproofing & Bonding Agent

Product Name	Product Description	Usage of Product	Dosages/ Coverage/Yield	Pack Size
Ultra CG	Plasticised Expanding grout Admixture complying with BS:8110 Part 1-1985,section8.9.4.6.	Reduce Water/Cement ratio mixes in the grout mix,Gives high fluidity with low W/C ratio,composition allows high early strength development in grout.	01 packet per 50 kg cement	225 g packet & in 25 kg pack
Grout EP	Ultra High Strength Pourable Epoxy Resin Grout	Grout EP is 03 component highly filled free flowing epoxy grout.It is used for tracks,heavy machinery,fixing bolts and anchor.	10 Kg.pack yeild approximately 05 liter of grout( 03 Component)	10 Kg packs
Ultra LV	Low Viscosity epoxy injection grout	structure crack repair	Refer Data Sheet	01 liter
ULTRASUPER SBR	Mortar and Screed modifier cum bonding aid complying with BS 6319 & wet cured	For Modifying and improving bonding of floor topings, renderings and mortars, waterproof plaster for masonry.	05 liter/50 kg of cement	05, 20 liter Packs
Ultra Crete	Ultracrete is an acrylic co-polymer emulsion for cementitious composite coating system.	It is mostly used for roof waterproofing ,pile head waterproofing, waterproofing of portable water reservoirs.	05 to 3 Sq.mtr.in two coats if applied brush application	05 and 20 liter packs
Ultramol IWL	Integral Waterproofing Liquid Admixture	To minimize permeability and increase waterproofing properties of concrete and cement sand mortar	Refer Data Sheet	50 and 200 kg barrels





Grouts and Waterproofing & Bonding Agent

Product Name	Product Description	Usage of Product	Dosages/ Coverage/Yield	Pack Size
Ultra Plug	Rapid/Extra fast setting/ hardening, chloride free compound for waterproofing/leak plugging in cement mortar & concrete.	Quick fixing of Injection nozzles; To stop strong localized water leakage through concrete e.g. Dams , Water reservoirs basement, Pipe joint, Retaining tunnels, Sewage Work etc where water is leaking under pressure;	For fast setting 35-40% by weight of cement. It need not be diluted with water; For fast setting of concrete, early release of shuttering,winter concreting it may be diluted and used Successfully after conducting necessary site trials	20 & 225 kg Containers
Ultra Fix C	Normal/ Fast setting high strength cement capsule, Specially meant for installing anchor bolts etc.	Provides higher strength and has greater resistance to Sulphonate Attack then ordinary cement, Easy to use in tube form; Can be used near freezing temperatures. <i>Shelf life: 06Months.</i>	25 X 300 mm, 32 X 300 mm, 40 X 300 mm.	25 capsules in Polythene pack and 2 packs in one Carton
Ultra Fiber Flex	ULTRAFIBER FLEX is a two component elastomeric coating waterproofing system based on cementitious binders reinforced with compatible micro fibers, special additives, fine-grained selected aggregates, high grade acrylic polymers to provide superior water protection.	Sealing fine cracks; Ideal material for roof, Terrace garden waterproofing with sand witted glass fiber; Most effective for damp proofing, arresting carbonation, Efflorescence over concrete, mortar, Brick work, Block work or similar surfaces;	16-18 m <sup>2</sup> /25 kg pack in 2 coats.	25kg Kit
Ultra Coat	Clear, Aliphatic acrylic resin based water repellent coating for exterior exposed surfaces.	Suitable for concrete block, concrete, brick, stone, cement plaster. Prevents moisture damage to interior surfaces such as plaster cracking and paint blistering. Will also restore color and reseal all panels.	15-18 m <sup>2</sup> /Litre in one coat depending on porosity and type of surface.	5 & 20 ltrdrum
Ultra Coat RTU	Ready-to-use water/solvent based colorless silicone water repellent coating for impregnation of exterior walls which, when applied, creates a highly water repellent surface.	Most effective on any siliceous surface, old or new; Ready to use by brush or spray; Reduces risk of efflorescence, lime erosion, rust staining, direct collection, formulation of mild dew, moss lichen and frost spalling; Preserves natural colour and texture of treated substrates;	18 - 20 m <sup>2</sup> / Litre depending on the porosity of the substrate surface	5, 25 & 225 L containers
Ultra Coat CP	Ready to use, two pack polymer modified cementitious coating having excellent corrosion protection capability on reinforcement & concrete surface.	Easy application with brush; Excellent adhesion with steel and concrete; Can be used on concrete surface for corrosion protection against Weathering effect; Excellent for repair of damaged concrete. <i>Shelf life: 06 Months.</i>	3 kg kit will cover 1.6 -1.8 m <sup>2</sup> for 1mm thickness.	3, 15 & 30 kg kit





Product Name	Product Description	Usage Of Product	Dosages/ Coverage/Yield	Pack Size
EZY SLIP AID	Concrete Pumping Aid (Slurry Pouch)	Used for pump priming, increase ease and range of pump ability	01 pack with 25 liter of water to prime 70 mtr of 05 inch pump line	250 gm packets
Grout EP	Ultra High Strength Pourable Epoxy Resin Grout	Grout EP is 03 component highly filled free flowing epoxy grout. It is used for tracks, heavy machinery, fixing bolts and anchor.	10 Kg. pack yeild approximately 05 liter of grout( 03 Component)	10 Kg packs
Ultra LV	Low Viscosity epoxy injection grout	structure crack repair	Refer Data Sheet	01 liter
ULTRASUPER SBR	Mortar and Screed modifier cum bonding aid complying with BS 6319 & wet cured	For Modifying and improving bonding of floor topings, renderings and mortars, waterproof plaster for masonry.	05 liter/50 kg of cement	05, 20 liter Packs
Ultra Crete	Ultra Crete is an acrylic co-polymer emulsion for cementitious composite coating system.	It is mostly used for roof waterproofing ,pile head waterproofing, waterproofing of portable water reservoirs.	05 to 3 Sq.mtr.in two coats if applied brusha application	05 and 20 liter packs
Ultramar IWL	Integral Waterproofing Liquid Admixture	To minimize permeability and increase waterproofing properties of concrete and cement sand mortar	Refer Data Sheet	50 and 200 kg barrels



## Protective Coatings

Product Name	Product Description	Usage Of Product	Dosages/ Coverage/Yield	Pack Size
Ultra Coat	Clear, Aliphatic acrylic resin based water repellent coating for exterior exposed surfaces.	Suitable for concrete block, concrete, brick, stone, cement plaster. Prevents moisture damage to interior surfaces such as plaster cracking and paint blistering.	15-18 m <sup>2</sup> /Litre in one coat depending on porosity and type of surface.	5 & 20 ltr drum
Ultra Prime	ULTRAPRIME weatherproof exterior emulsion is a 100% acrylic water based emulsion with excellent UV stability properties.	ULTRAPRIME weatherproof exterior emulsion is a high performance, long-lasting exterior paint specially formulated to withstand extreme tropical conditions of high rainfall, humidity and heat. <i>Shelf life: 18 Months.</i>	On normal masonry surface by brushing 1 Coat : 10.5 - 11.5m <sup>2</sup> /Litre 2 Coats : 5.5 - 6m <sup>2</sup> /Litre	4 & 20 Litre
Ultra ES	A two part chemically cured, water based epoxy sealer membrane for most porous building components	For curing, seepage and dampness problems on interior or exterior surfaces of basements, tunnels, lift wells, retaining walls, floors, below grade car parks, etc.	9 m <sup>2</sup> /Kg for 0.5 mm thickness	9 m <sup>2</sup> /Kg for 0.5 mm thickness
ULTRAZINC P	Low viscosity, Two component epoxy resin based zinc rich epoxy primer.	For exposed steel surface of marine decks and structures, tanks, concrete reinforcement along with concrete repair mortars etc. Highly corrosion inhibitor which provides galvanic protection against corrosion.	3.8-4.5 m <sup>2</sup> /Litre /Coat depending upon surface texture & porosity.	6, 20 Kg & bulk packing
Ultra Coat CP	Ready to use, two pack polymer modified cementitious coating having excellent corrosion protection capability on reinforcement & concrete surface.	Easy application with brush; Excellent adhesion with steel and concrete; Can be used on concrete surface for corrosion protection against weathering effect; Excellent for repair of damaged concrete. <i>Shelf life: 06 Months.</i>	: 3 kg kit will cover 1.6 - 1.8 m <sup>2</sup> for 1mm thickness.	3, 15 & 30 kg kit
Ultra Coat PU	Integral Waterproofing Liquid Admixture	To minimize permeability and increase waterproofing properties of concrete and cement sand mortar	Refer Data Sheet	50 and 200 kg barrels



## Surface Treatments

Product Name	Product Description	Usage Of Product	Dosages/ Coverage/Yield	Pack Size
Ultra Cure WB	Ready to use, two pack polymer modified cementitious coating having excellent corrosion protection capability on reinforcement & concrete surface.	Protection of reinforcement of isolated footings and columns located inside soil specially for areas where the soil is having agricultural chemicals.	3 kgkit will cover 1.6 to 1.8 m <sup>2</sup> for 1mm thickness.	3, 15 & 30 kg kit
Ultra Cure AL	Resin based Aluminized liquid membrane curing compound for concrete. Conforms to BS:7542-1992, ASTM: C 309- 07.	On freshly cast concrete or newly exposed concrete after removal of formwork; Suitable for all general concrete applications particularly for large area of concrete surface such as pavements, runways, bridge decks, roads etc.	Steel troweled surface : 9 -11m <sup>2</sup> /Litre.	25 & 200 Litre
Ultra Lease	Specially formulated with high grade natural organic chemicals, highly concentrated mould release agent for easy, stain free, assured high quality surface finish.	On steel, plastic, wooden formwork for clean release; Minimum shutter cleaning; Increased shutter age; Can be applied with brush, sprayer, squeegee.	Steel / plastic surface: 100-200 m <sup>2</sup> /Litre Wooden surface: 80-100 m <sup>2</sup> /Litre (When diluted with water in 1:5 ratio).	5, 20 & 200 Litre
Ultra Lease RTU	Specially formulated, ready to use, blended with high grade natural organic chemicals and mineral oil, mould release agent for easy, stain free, assured high quality surface finish.	On steel, plastic, wooden formwork for clean release, minimum shutter cleaning, Age of shutter increased, can be applied with brush, sprayer, squeegee.	Steel /plastic surface: 90-100m <sup>2</sup> /Litre Wooden surface: 15-20 m <sup>2</sup> /Litre.	4 & 25 Litre
Ultra Lease OB	Ready to use specially formulated mineral based mould release oil of sprayable consistency for assured high quality surface finish.	On steel, plastic, wooden formwork for easy and clean release; Minimum shutter cleaning cost; Increased shutter life; Can be applied with brush, sprayer, squeegee; Preserves uniformity of surface texture & color.	Steel/plastic surface: 20-25 m <sup>2</sup> /Litre	5, 20 & 200 Litre



**SEALANTS**

Product Name	Product Description	Usage Of Product	Dosages/ Coverage/Yield	Pack Size
Ultra Seal PG	Two component polysulphide based construction joint sealant; BS: 4254-1983, ASTM C920-10, IS:12118- 1987 (Part I & II).	For horizontal expansion joints where large movements are anticipated Also for different construction materials like steel, aluminum, glass, cladding, glazing, tiling, tanks and water retaining structures. It is used for sealing expansions, joints in airport runways, roads & bridges. (Specific Gravity 1.65).	1 & 4 kg Pack	1 & 4 kg Pack
Ultra Seal GG	Two component polysulphide based construction joint sealant; BS: 4254-1983, ASTM C920-10, IS:12118- 1987 (Part I & II).	For vertical expansion joints, Also for different construction materials like steel, aluminum, glass, cladding, glazing, tiling, tanks and water retaining structures. (Specific Gravity 1.62).	1 & 4 kg Pack	1 & 4 kg Pack
Ultra Seal CS	Acrylic sealant is a white Acrylic Fiber Reinforced Crack Sealer in paste form for sealing wall cracks on plastered surfaces.	Easy to apply and finish, excellent adhesion to most building materials fast setting, non-staining, flexible seal, can be over painted or papered. <i>Shelf life: 12 Months.</i>	500g & 1kg Pack	500g & 1kg Pack
Ultra Tile Fix	Single pack polymer modified cementitious system, used as an excellent tile adhesive.	For ceramic and mosaic tile bonding (both exterior and interior) places such as bathrooms, toilets, shower recesses, laundries and swimming pool. Most suitable applied over rendered brick work, masonry and concrete surfaces.	13-14 kg/m <sup>2</sup> when applied by 7mm notched trowel	25 kg pack
Ultra Tile Fix	A cementitious tile adhesive is a multi-purpose polymer fortified thin set powder to be mixed only with water to install various types of tiles and stones on variety of substrates.	It should be spread on the substrate to a uniform thickness of 2-3mm, and then combed horizontally with a serrated trowel. Place tiles firmly in to adhesive bed, ensuring good contact with a twisting motion and beat in using a beating block or rubber mallet to embed tile and adjust level.	Approx. 3.8 kg / m <sup>2</sup> @ 2mm on a levelled floors	1 & 4 kg Pack (A+B)





**Government of India**  
**Form GST REG-06**  
[See Rule 10(1)]  
**Registration Certificate**

**Registration Number :** 09CDXPS9452A4ZR

1.	<b>Legal Name</b>	pitam chaudhary			
2.	<b>Trade Name, if any</b>	ULTRASUPER CHEMICAL COMPANY			
3.	<b>Constitution of Business</b>	Proprietorship			
4.	<b>Address of Principal Place of Business</b>	0, MAUJA MAHOLI ANDRUN, MILAN VATIKA COLONY, Mathura, Uttar Pradesh, 281001			
5.	<b>Date of Liability</b>				
6.	<b>Period of Validity</b>	From	21/10/2021	To	Not Applicable
7.	<b>Type of Registration</b>	Regular			
8.	<b>Particulars of Approving Authority</b>	Centre			
Signature		Signature Not Verified Digitally signed by DS GOODS AND SERVICES TAX NETWORK(4) Date: 2021.10.21 16:30:41 IST			
Name		Ajay Sharma			
Designation		Superintendent			
Jurisdictional Office		Mathura Sector-6			
9. Date of issue of Certificate		21/10/2021			
Note: The registration certificate is required to be prominently displayed at all places of business in the State.					

This is a system generated digitally signed Registration Certificate issued based on the approval of application granted on 21/10/2021 by the jurisdictional authority.



TIN No. 24180402103  
CST No. 24680402103

## BSCPL Infrastructure Limited

BSCPL

Site Office : NH-59, KM-184+000, Vill. Rampura,  
Ta. & Dist. Dahod-389151 (Gujarat) E-mail: bscpl\_godhra@yahoo.com

Phone : +91-8128650411



P.O NO: BSCPL/PO/GJ/11-12/15/3050

Date: 12<sup>th</sup> Dec, 2011

To  
M/S Sun Chem,  
103, Khatri house, near heena arcade,  
GIDC char rasta VAPI,  
Gujarat-396195.

Kind Attn: - Mr. Pritam Chaudhary

Project: - A lanning of Godhra to Gujarat/Madhya Pradesh Border Section of NH-59, from km  
129.300 to km 215.900 in the state of Gujarat on Design, Build, Finance, Operate and  
Transfer ("DBFOT") basis under NHDP III".

Subject : Purchase Order for Supply of Ultracon-53 PQC Admixture Reg:-  
Ref : Your quotation by E-Mail Dated: 23-11-11.

Dear Sir,  
With reference to the above cited subject, we are pleased to place an order for Supply of the  
ULTRACON -58, PQC Admixture for The above Road Project.

S.No	Description	Quantity Delivery at Rampuar	Quantity Delivery at Piplod	Total Qty	Rate per MT
1	ULTRA-58 PQC (PQC ADMIXTURE)	10M.T	10M.T	20M.T	

### Terms & Conditions:

Price : The above rates are Inclusive of Excise duty & Gujarat Vat & Empty Barrels.  
Transportation : F.O.R at our site.  
Payment : Payment will be made 30 Days after Material Received at the site.  
Test Certificate : Test Certificate should be produced along with Challan.  
Delivery : Immediately.  
Quality : Replacement of entire lot in case of failure in 3<sup>rd</sup> party Test Report.  
Billing Address : BSCPL Infrastructure Limited  
NH-59, Vill: Rampura, Th. & Dist. Dahod - 389151 (GJ).  
Ph: 8128650411, 81828681228 E mail: bscpl\_godhra@yahoo.com.bscpl\_godhra1@yahoo.com

Thanking you,

With regards,  
For BSCPL Infrastructure limited.

J. Nagendra Kumar  
Project Manager

K.Rambabu  
Project Site In charge

Registered Office : #6-2-913/914, 5th Floor, Progressive Towers, Khairatabad, HYDERABAD-500 004 (A.P.) INDIA  
Ph. Off. (91-40) 23307831, 23307704, 23303663 Fax : 040-23307385  
E-mail : bscpl@satyam.net.in

**P. S. CONSTRUCTIONS** PEE ESS  
ISO 9001 : 2008

Specialist in : All Types of Civil Constructions, Fabrication & Errection

Head Office : Opp. Railway Power Grid, Sahnewal, Ludhiana - 141 120 (Pb.)  
Ph. : (O) 0161-2844554, E-mail : psconstructions\_1@yahoo.co.in

Dated 04.01.2014

Ref. No. ....

To  
**The Manager Marketing,**  
**Ultracon Conschem Pvt.Ltd.**  
**Bharatpur (Raj.)**

**Sub: - Purchase order for Admixtures.**

**Dear Sirs**

With the reference of your Quotation No.NR/ULTRACON/2013-J.P./009 Dated. 20.06.2013 and telephonic discussion with Mr. J.P.Singh (Business head) of your company (North).

We Pleased to place a order for admixture i.e. Ultra Super 58001, Ultra Super 58002 (product code) for regular supply at our Manegaon plant in Jabalpur (M.P.) as under:-

S.No.	Product	Brief Description	Unit	Rate's per Kg. (In Rs.)	
1	Ultra Super58001	Admixture	Kg.	... kg.	
2	Ultra Super58002	Admixture	Kg.	... kg.	

**You requested please to send ULTRA SUPER 58002 (Product Code) in first consignment of 40-Drums (10.00MT)**

1. Above prices is including all taxes and duties, material delivery F O R at Manegaon in Jabalpur (M.P.) at our RMC Plant.
2. Cartage will be borne by you.
3. Unloading will be on our part.
4. Form C and road permit will be provided by us.
5. Payment will be made after 15-days of delivery of material.
6. Delivery time maximum 3-Days.

(We assure to you our best cooperation)  
Thanking You

Yours Faithfully  
**For P.S. CONSTRUCTIONS.**

*MS Singh 4/1/2014*  
Authorized Signatory

B/O : H-13, Beta-II, Greater Noida-201 308 (U.P.) Ph : (O) 0120-4292991, TIN : 09866301116  
B/O : Infront Chaurasia Hospital, Nahar Wali Mata Ke Neeche, Naka Chandrabandi Lashkar Town/City - Gwalior, (M.P.)  
Mob.: 08800897702 Tin - 23409055196  
B/O : Koshalya Vihar-201, 2nd Floor, 785, 786, Napier Town, Jabalpur-482001 (M.P.) Ph. 0761-4072119

[www.psconstructionsindia.com](http://www.psconstructionsindia.com)



**Sole Distributor For Nepal**  
**Elite Traders Pvt. Ltd.**

📍 Sokedhara-4, Kathmandu, Nepal

✉ sales.etpln@gmail.com, Website: [www.etpln.com](http://www.etpln.com)

📞 01-4650186, +977-9849904677